

# WD-304 LCD Customer Display

## FEATURES



- \* CCFL back light.
- \* Data can be displayed on 30 columns x 4 lines.
- \* Display panel is adjustable to provide the best view angle.
- \* Provide 2 poles for the best position installation.
- \* Esc/pos command compatible.
- \* International characters set is selectable.
- \* Provides interface on RS-232C.
- \* Built-in pass through function.
- \* Wide range power input from 9 to 35VDC.
- \* The Chinese, Korean, Japanese and Thailand characters are ready.
- \* Dimensions: 225W x 10D x 560H (max.) mm.
- \* Provide small round base and plant easy to combine with POS terminal.

## SPECIFICATIONS



<b>Power supply</b>	DC 9 - 30 V	
<b>LCD type</b>	STN Blue mode	
<b>Backlight mode</b>	CCFL backlight	
<b>Brightness</b>	100 cd/m <sup>2</sup>	
<b>Display color</b>	Blue and White	
<b>Character size</b>	9.0mm X 5.25mm	
<b>Number of character</b>	30 columns x 4 lines alphanumeric 15 columns x 4 lines Chinese character ( or double high is 2 lines )	
<b>Character font</b>	8 x 16 Dot matrix by alphanumeric 16 x 16 dot-matrix by Chinese character	
<b>Character size</b>	8.47 x 4.24mm ( 16x8 dot )	
	8.47 x 8.47mm ( 16x16dot )	
	16.9 x 8.47mm ( 32x16 dot )	
<b>Power consumption</b>	3 - 6 W	
<b>MTBF (power on)</b>	15000 hours	
<b>Viewing angle</b>	0 - 45 degrees	
<b>Rotation angle</b>	Maximum 270 degrees	
<b>Weight</b>	0.90 Kg	
<b>Environmental</b>	<b>Temperature</b>	<b>Humidity</b>
<b>Operating</b>	5 - 45 °C	30% - 85%
<b>Storage</b>	-10 - 55 °C	30% - 85%

